



CENTARA

Mittelschlussheizkörper

Wärmeleistung

BL / mm	Bauhöhe / mm Typ	350		500				600				900				BL / mm
		22	33	20	21	22	33	20	21	22	33	20	21	22	33	
400	Bestell-Nr.			21-500420	21-500421	21-500422		21-600420	21-600421	21-600422		21-900420	21-900421	21-900422		
	Watt 75°/65°/20°			322	413	515		367	477	614		515	588	771		
	Watt 70°/55°/20°			259	334	418		294	386	497		412	474	620		
500	Bestell-Nr.			21-500520	21-500521	21-500522	21-500533	21-600520	21-600521	21-600522	21-600533	21-900520	21-900521	21-900522	21-900533	
	Watt 75°/65°/20°			403	517	644	972	459	596	768	1074	644	736	964	1384	
	Watt 70°/55°/20°			324	418	523	785	368	483	621	865	515	593	775	1110	
600	Bestell-Nr.			21-500620	21-500621	21-500622	21-500633	21-600620	21-600621	21-600622	21-600633	21-900620	21-900621	21-900622	21-900633	
	Watt 75°/65°/20°			483	620	772	1166	550	715	922	1289	773	883	1157	1661	
	Watt 70°/55°/20°			388	502	628	942	442	580	745	1037	618	711	929	1332	
700	Bestell-Nr.			21-500720	21-500721	21-500722	21-500733	21-600720	21-600721	21-600722	21-600733	21-900720	21-900721	21-900722	21-900733	
	Watt 75°/65°/20°			564	723	901	1360	642	834	1075	1504	902	1030	1350	1938	
	Watt 70°/55°/20°			453	585	732	1099	515	676	869	1210	721	830	1084	1554	
800	Bestell-Nr.	21-350822	21-350833	21-500820	21-500821	21-500822	21-500833	21-600820	21-600821	21-600822	21-600833	21-900820	21-900821	21-900822	21-900833	
	Watt 75°/65°/20°	910	1334	644	826	1030	1554	734	954	1229	1718	1030	1177	1542	2214	
	Watt 70°/55°/20°	729	1059	518	669	837	1256	589	773	994	1383	824	948	1239	1776	
900	Bestell-Nr.			21-500920	21-500921	21-500922	21-500933	21-600920	21-600921	21-600922	21-600933	21-900920	21-900921	21-900922	21-900933	
	Watt 75°/65°/20°			725	930	1158	1749	825	1073	1382	1933	1159	1324	1735	2491	
	Watt 70°/55°/20°			582	752	941	1413	662	869	1118	1556	927	1067	1394	1998	
1000	Bestell-Nr.	21-351022	21-351033	21-501020	21-501021	21-501022	21-501033	21-601020	21-601021	21-601022	21-601033	21-901020	21-901021	21-901022	21-901033	
	Watt 75°/65°/20°	1137	1667	805	1033	1287	1943	917	1192	1536	2148	1288	1471	1928	2768	
	Watt 70°/55°/20°	911	1324	647	836	1046	1570	736	966	1242	1729	1030	1185	1549	2220	
1200	Bestell-Nr.	21-351222	21-351233	21-501220	21-501221	21-501222	21-501233	21-601220	21-601221	21-601222	21-601233			21-901222		
	Watt 75°/65°/20°	1364	2000	966	1240	1544	2332	1100	1430	1843	2578			2314		
	Watt 70°/55°/20°	1093	1589	776	1003	1255	1884	883	1159	1490	2075			1859		
1400	Bestell-Nr.	21-351422	21-351433	21-501420	21-501421	21-501422	21-501433	21-601420	21-601421	21-601422	21-601433			21-901422		
	Watt 75°/65°/20°	1592	2334	1127	1446	1802	2720	1284	1669	2150	3007			2699		
	Watt 70°/55°/20°	1275	1854	906	1170	1464	2198	1030	1352	1739	2421			2169		
1600	Bestell-Nr.	21-351622	21-351633	21-501620	21-501621	21-501622	21-501633	21-601620	21-601621	21-601622	21-601633					
	Watt 75°/65°/20°	1819	2667	1288	1653	2059	3109	1467	1907	2458	3437					
	Watt 70°/55°/20°	1458	2118	1035	1338	1674	2512	1178	1546	1987	2766					
1800	Bestell-Nr.	21-351822	21-351833	21-501820	21-501821	21-501822	21-501833	21-601820	21-601821	21-601822	21-601833					
	Watt 75°/65°/20°	2047	3001	1449	1859	2317	3497	1651	2146	2765	3866					
	Watt 70°/55°/20°	1640	2383	1165	1505	1883	2826	1325	1739	2236	3112					
2000	Bestell-Nr.	21-352022	21-352033	21-502020	21-502021	21-502022		21-602020	21-602021	21-602022						
	Watt 75°/65°/20°	2274	3334	1610	2066	2574		1834	2384	3072						
	Watt 70°/55°/20°	1822	2648	1294	1672	2092		1472	1932	2484						
2200	Bestell-Nr.	21-352222	21-352233			21-502222				21-602222						
	Watt 75°/65°/20°	2501	3667			2831				3379						
	Watt 70°/55°/20°	2004	2913			2301				2732						
2600	Bestell-Nr.	21-352622	21-352633			21-502622				21-602622						
	Watt 75°/65°/20°	2956	4334			3346				3994						
	Watt 70°/55°/20°	2369	3442			2720				3229						
3000	Bestell-Nr.	21-353022	21-353033			21-503022				21-603022						
	Watt 75°/65°/20°	3411	5001			3861				4608						
	Watt 70°/55°/20°	2733	3972			3138				3726						
bezogen auf BL 1000mm	Watt 75°/65°/20°	1137	1667	805	1033	1287	1943	917	1192	1536	2148	1288	1471	1928	2768	
	Watt 70°/55°/20°	911	1324	647	836	1046	1570	736	966	1242	1729	1030	1185	1549	2220	
	Watt 55°/45°/20°	579	827	414	542	685	1015	470	629	804	1109	652	761	989	1414	
	Exponent n	1,3044	1,3568	1,2854	1,2469	1,2214	1,2572	1,2926	1,2363	1,2515	1,2794	1,3171	1,2749	1,2914	1,2993	
	Wasserinhalt in l	2,80	4,10	3,60	3,60	3,60	5,80	4,40	4,40	4,40	6,70	6,40	6,40	6,40	9,60	
Gewicht in kg		24,40	35,60	21,90	25,20	29,30	43,40	26,10	30,40	34,70	51,50	40,80	43,10	49,40	73,00	

