

CLASSIC M plan

Mittelschlussheizkörper

Wärmeleistung

Baulänge / mm	Bauhöhe / mm Typ	300		500				600				900				Baulänge / mm	
		22	33	20	21	22	33	20	21	22	33	20	21	22	33		
400	Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°			31-500420-p 314 252 160				31-600420-p 362 290 184	31-600421-p 476 381 243	31-600422-p 626 501 316		31-900420-p 504 404 256	31-900421-p 634 506 320	31-900422-p 794 635 401	31-900433-p 1098 875 549	400	
	Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°			31-500520-p 393 315 201	31-500521-p 512 411 262	31-500522-p 679 543 344		31-600520-p 452 363 231	31-600521-p 595 477 304	31-600522-p 783 626 396		31-900520-p 631 505 320	31-900521-p 792 633 401	31-900522-p 993 794 502	31-900533-p 1373 1094 686		500
	Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°			31-500620-p 472 378 241	31-500621-p 614 493 314	31-500622-p 814 651 412	31-500633-p 1070 856 542	31-600620-p 542 435 277	31-600621-p 713 572 364	31-600622-p 940 751 475	31-600633-p 1237 989 625	31-900620-p 757 605 383	31-900621-p 950 760 481	31-900622-p 1192 952 602	31-900633-p 1648 1312 823		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°				31-500721-p 717 575 366	31-500722-p 950 760 481		31-600720-p 633 508 323	31-600721-p 832 667 425	31-600722-p 1096 876 554	31-600733-p 1443 1154 729	31-900720-p 883 706 447	31-900721-p 1109 886 561	31-900722-p 1390 1111 702	31-900733-p 1922 1531 960	700		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-300822-p 759 602 376	31-300833-p 1097 870 542	31-500820-p 629 504 321	31-500821-p 819 657 418	31-500822-p 1086 868 550	31-500833-p 1427 1142 722	31-600820-p 723 580 369	31-600821-p 951 762 486	31-600822-p 1253 1002 633	31-600833-p 1650 1318 834	31-900820-p 1009 807 511	31-900821-p 1589 1270 802	31-900822-p 2197 1750 1098	31-900833-p 2471 1968 1235		800	
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°					31-500922-p 1221 977 618	31-500933-p 1606 1284 813	31-600920-p 814 653 415	31-600921-p 1070 858 546	31-600922-p 1409 1127 712	31-600933-p 1856 1483 938		31-900922-p 1787 1428 903	31-900933-p 2471 1968 1235	900			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301022-p 949 753 470	31-301033-p 1371 1088 678	31-501020-p 786 630 401	31-501021-p 1024 821 523	31-501022-p 1357 1085 687	31-501033-p 1784 1427 903	31-601020-p 904 725 461	31-601021-p 1189 953 607	31-601022-p 1566 1252 791	31-601033-p 2062 1648 1042		31-901022-p 1986 1587 1003	31-901033-p 2746 2187 1372		1000		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301222-p 1139 904 564	31-301233-p 1645 1306 814	31-501221-p 1229 985 628	31-501222-p 1628 1302 824	31-501233-p 2141 1712 1084		31-601220-p 1085 870 553	31-601221-p 1427 1144 728	31-601222-p 1879 1502 949	31-601233-p 2474 1978 1250		31-901222-p 2383 1904 1204				1200	
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301422-p 1329 1054 658	31-301433-p 1919 1523 949	31-501421-p 1434 1149 732	31-501422-p 1900 1519 962	31-501433-p 2498 1998 1264		31-601421-p 1665 1334 850	31-601422-p 2192 1753 1107	31-601433-p 2887 2307 1459					1400			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301622-p 1518 1205 752	31-301633-p 2194 1741 1085	31-501621-p 1638 1314 837	31-501622-p 2171 1736 1099	31-501633-p 2854 2283 1445		31-601621-p 1902 1525 971	31-601622-p 2506 2003 1266	31-601633-p 3299 2637 1667						1600		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301822-p 1708 1355 846	31-301833-p 2468 1958 1220		31-501822-p 2443 1953 1237	31-501833-p 3211 2569 1625		31-601821-p 2140 1715 1093	31-601822-p 2819 2254 1424	31-601833-p 3712 2966 1876							1800	
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-302022-p 1898 1506 940	31-302033-p 2742 2176 1356		31-502022-p 2714 2170 1374	31-502033-p 3568 2854 1806		31-602021-p 2378 1906 1214	31-602022-p 3132 2504 1582						2000			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°		31-302233-p 3016 2394 1492		31-502222-p 2985 2387 1511			31-602222-p 3445 2754 1740								2200		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°																2600	
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°														3000			
bezogen auf Baulänge 1000mm	Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20° Exponent n Wasserinhalt in l Gewicht in kg	949 753 470 1,3591 3,40 16,20	1371 1088 678 1,3613 5,10 24,20	786 630 401 1,2999 5,20 20,90	1024 821 523 1,2992 5,20 24,80	1357 1085 687 1,3158 5,30 29,20	1784 1427 903 1,3162 8,00 43,50	904 725 461 1,3029 6,10 25,10	1189 953 607 1,2992 6,10 30,00	1566 1252 791 1,3208 6,30 35,70	2062 1648 1042 1,3196 9,40 53,20	1261 1009 639 1,3143 9,10 37,60	1584 1266 801 1,3193 9,10 42,90		1986 1587 1003 1,3215 9,20 48,70		2746 2187 1372 1,3427 13,10 74,90