



CLASSIC M

Mittelschlussheizkörper

Wärmeleistung

Baulänge / mm	Bauhöhe / mm Typ	300		500				600				900				Baulänge / mm			
		22	33	20	21	22	33	20	21	22	33	20	21	22	33				
400	Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°			31-500420 338 271 173				31-600420 389 312 198	31-600421 511 410 261	31-600422 674 538 340				31-900420 542 434 275	31-900421 681 544 344	31-900422 854 683 432	31-900433 1181 940 590	400	
	Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°			31-500520 423 339 216	31-500521 551 442 282	31-500522 730 584 370		31-600520 486 390 248	31-600521 639 513 327	31-600522 842 673 426				31-900520 678 543 344	31-900521 852 681 431	31-900522 1068 854 540	31-900533 1477 1176 738		500
	Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°			31-500620 507 407 259	31-500621 661 530 338	31-500622 875 700 443	31-500633 1151 920 583	31-600620 583 467 298	31-600621 767 615 392	31-600622 1010 808 511	31-600633 1330 1063 673	31-900620 814 651 412	31-900621 1022 817 517	31-900622 1282 1024 647	31-900633 1772 1411 885	600			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°				31-500721 771 618 394	31-500722 1021 817 517		31-600720 680 545 347	31-600721 895 718 457	31-600722 1179 942 596	31-600733 1552 1240 785	31-900720 949 760 481	31-900721 1192 953 603	31-900722 1495 1195 755	31-900733 2067 1646 1033	700				
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-300822 816 648 404	31-300833 1179 936 583		31-500820 676 542 346	31-500821 881 706 450	31-500822 1167 934 591	31-500833 1534 1227 777	31-600820 778 623 397	31-600821 1022 820 522	31-600822 1347 1077 681	31-600833 1774 1418 897	31-900820 1085 868 550		31-900822 1709 1366 863			31-900833 2362 1881 1180	800	
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°					31-500922 1313 1050 665	31-500933 1726 1381 874		31-600920 875 701 446	31-600921 1150 923 588	31-600922 1516 1211 766	31-600933 1995 1595 1009			31-900922 1922 1536 971		31-900933 2658 2116 1328	900		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301022 1020 810 505	31-301033 1474 1170 729		31-501020 845 678 432	31-501021 1101 883 563	31-501022 1459 1167 739	31-501033 1918 1534 971	31-601020 972 779 496	31-601021 1278 1025 653	31-601022 1684 1346 851	31-601033 2217 1772 1121			31-901022 2136 1707 1079	31-901033 2953 2351 1475	1000			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301222 1224 972 606	31-301233 1769 1404 875		31-501221 1321 1060 676	31-501222 1751 1400 887	31-501233 2302 1841 1165		31-601220 1166 935 595	31-601221 1534 1230 784	31-601222 2021 1615 1021	31-601233 2660 2126 1345			31-901222 2563 2048 1295	1200				
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301422 1428 1134 707	31-301433 2064 1638 1021		31-501421 1541 1236 788	31-501422 2043 1634 1035	31-501433 2685 2148 1359			31-601421 1789 1435 914	31-601422 2358 1884 1191	31-601433 3104 2481 1569						1400		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301622 1632 1296 808	31-301633 2358 1872 1166		31-501621 1762 1413 901	31-501622 2334 1867 1182	31-501633 3069 2454 1554			31-601621 2045 1640 1045	31-601622 2694 2154 1362	31-601633 3547 2835 1794					1600			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-301822 1836 1458 909	31-301833 2653 2106 1312			31-501822 2626 2101 1330	31-501833 3452 2761 1748			31-601821 2300 1845 1175	31-601822 3031 2423 1532	31-601833 3991 3190 2018				1800				
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°	31-302022 2040 1620 1010	31-302033 2948 2340 1458			31-502022 2918 2334 1478	31-502033 3836 3068 1942			31-602021 2556 2050 1306	31-602022 3368 2692 1702							2000		
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°		31-302233 3243 2574 1604			31-502222 3210 2567 1626					31-602222 3705 2961 1872						2200			
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°															2600				
Bestell-Nr. Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20°																	3000		
bezogen auf Baulänge 1000mm	Watt 75°/65°/20° Watt 70°/55°/20° Watt 55°/45°/20° Exponent n Wasserinhalt in l Gewicht in kg	1020 810 505 1,3591 3,40 16,20	1474 1170 729 1,3613 5,10 24,20	845 678 432 1,2999 5,20 20,90	1101 883 563 1,2992 5,20 24,80	1459 1167 739 1,3158 5,30 29,20	1918 1534 971 1,3162 8,00 43,50	972 779 496 1,3029 6,10 25,10	1278 1025 653 1,2992 6,10 30,00	1684 1346 851 1,3208 6,30 35,70	2217 1772 1121 1,3196 9,40 53,20	1356 1085 687 1,3143 9,10 37,60	1703 1361 861 1,3193 9,10 42,90	2136 1707 1079 1,3215 9,20 48,70		2953 2351 1475 1,3427 13,10 74,90		bezogen auf Baulänge 1000mm	